








Twin Wheel Castors 38-80mm For Loads Up To 50kg

CAFORD
DESIGN

EASILY MOVED - ECONOMICAL - ATTRACTIVE - LARGEST RANGE IN NEW ZEALAND

	CODE	WHEEL Dia	MATERIAL	MAX LOAD	MOUNT HEIGHT	SWIVEL RADIUS	PLATE OR FITTING
		mm		KG	mm	mm	
	TWN38-138	38	nylon	20	45	30	Plate 38mm sq
	TWN38-7	38	nylon	20	45	30	Grip neck
	TWN38*- Threaded Pin	38	nylon	20	45	30	*(-9)5/16BSW,(-8)3/8BSW, or (-56)M8,all x20mm
	TWN42-138	42	nylon	25	55	40	Plate 38mm sq
	TWN42-7	42	nylon	25	55	40	Grip neck
	TWN42*- Threaded Pin	42	nylon	25	55	40	*(-9)5/16BSW,(-8)3/8BSW, or (-56)M8,all x20mm
	TWN50-138	50	nylon	30	60	45	Plate 38mm sq
	TWN50-2 & 2D	50	nylon	30	60	45	C/clip 5/16" dia
	TWN50-7	50	nylon	30	60	45	Grip neck
	TWN50*- Threaded Pin	50	nylon	30	60	45	*(-9)5/16BSW,(-8)3/8BSW, M10, or (-56)M8,all x20mm
	TWN50-6	50	nylon	30	60	45	3/8UNF x 50mm expanding fitting
	TWN80-145	80	nylon	50	100	70	Plate 45mm sq
	TWN80*- Threaded pin	80	nylon	50	95	70	*(-6)3/8UNF x 50mm Expanding fitting, (-4)1/2UNFx25mm
	Twn80Brake-145	80	nylon	50	100	70	Plate 45mm sq
	TWN80Brake- *Thread pin	80	nylon	50	95	70	*(-6)3/8UNF x 50mm Expanding fitting, (-4)1/2UNFx25mm



Caford NZ Ltd

Ph: +649 444 8334
 Fx: +649 444 0784
 E-mail: sales@caford.co.nz
 www.caford.co.nz

Hooded Twin Wheel Castors 42mm-60mm For Loads Up To 50kg

Caford Design

EASILY MOVED - ECONOMICAL - ATTRACTIVE - LARGEST RANGE IN NEW ZEALAND



CODE	WHEEL Dia	MATERIAL	MAX LOAD	MOUNT HEIGHT	SWIVEL RADIUS	PLATE OR FITTING
Hooded	mm		KG	mm	mm	
HTW42-138M	42	nylon	25	55	45	Plate 38mm sq
HTW42-7	42	nylon	25	55	45	Grip neck
HTW42-* Threaded Pin	42	nylon	25	55	45	*(-9)5/16BSW,(-8)3/8BSW, or M10,(-56)M8,all x20mm
HTW50-138M	50	nylon	30	60	50	Plate 38mm sq
HTW50-2 & 2D	50	nylon	30	60	50	5/16Dia Pin
HTW50-7	50	nylon	30	60	50	Grip neck
HTW50- * Threaded Pin	50	nylon	30	60	50	*(-9)5/16BSW,(-8)3/8BSW, or M10,(-56)M8,all x20mm & 3/8UNFx50mm
HTW60-138M	60	nylon	35	83	56	Plate 38mm sq
HTW60-7	60	nylon	35	83	56	Grip neck
HTW60- * Threaded Pin	60	nylon	35	83	56	*(-9)5/16BSW,(-8)3/8BSW, or M10,(-56)M8,all x20mm & (-6)3/8UNFx50mm







Twin Wheel Castors 30mm to 75mm For Loads Up To 50kg

Ph: +649 444 8334
Fx: +649 444 0784
E-mail:
sales@caford.co.nz
www.caford.co.nz

Imported
Design

EASILY MOVED - ECONOMICAL - ATTRACTIVE - LARGEST RANGE IN NEW ZEALAND

	CODE	WHEEL Dia	MATERIAL	MAX LOAD	MOUNT HEIGHT	SWIVEL RADIUS	PLATE OR FITTING
	Hooded	mm		KG	mm	mm	
	TW30-132M	30	nylon	15	40	35	Plate 32mm sq
	TW30-7	30	nylon	15	40	35	Grip neck
	TW30-M6* Threaded Pin	30	nylon	15	40	35	*M6x15mm
	ΓW40-138M	40	nylon	25	52	45	Plate 38mm sq
	ΓW40-7	40	nylon	25	52	45	Grip neck
	ΓW40- * Γhreaded Pin & U Bracket	40	nylon	25	52	45	*(-9)5/16BSW, (-8) 3/8BSW, & M10, (-56) M8, all x20mm, & M10x38 U16, 19 & 25mm
	ΓW50-138M	50	nylon	30	65	56	Plate 38mm sq
	ΓW50-7	50	nylon	30	65	56	Grip neck
	TW50- * Threaded Pin & U Bracket	50	nylon	30	65	56	**(-9)5/16BSW, (-8) 3/8BSW, & M10, (-56) M8, all x20mm, & M10x38 U16, 19 & 25mm 5/16BSW, 3/8BSW, r M10, M8, all x20mm, & M10x38 U16, 19 & 25mm
	Jn Hooded JTW75- 138M	75	nylon	50	82	64	Plate 45mm sq
	UTW75-7	75	nylon	50	82	64	Grip Neck
	UTW75-* Threaded Pin	75	Nylon	50	82	64	*3/8BSW, M10 all x20mm, & M10x38mm






Twin Wheel Castors 40mm to 75mm For Loads Up To 50kg

Ph: +649 444 8334
 Fx: +649 444 0784
 E-mail:
 swles@caford.co.nz
 www.caford.co.nz

Imported
Design

EASILY MOVED - ECONOMICAL - ATTRACTIVE - LARGEST RANGE IN NEW ZEALAND

BRAKE CASTORS

	CODE	WHEEL Dia	MATERIAL	MAX LOAD	MOUNT HEIGHT	SWIVEL RADIUS	PLATE OR FITTING
	Imported Hooded	mm		KG	mm	mm	
	TWB40-138M	40	nylon	25	40	35	Plate 32mm sq
	TWB40-7	34	nylon	25	40	35	Grip neck
	TWB40- *Threaded & U Bracket Pin	40	nylon	25	40	35	*5/16BSW, 3/8BSW, r M10, M8, all x20mm, & M10x38 U16, 19 & 25mm
	TWB50-138M	50	nylon	30	52	45	Plate 38mm sq
	TWB50-7	50	nylon	30	52	45	Grip neck
	TWB50- *Threaded & U Bracket Pin	50	nylon	30	52	45	**5/16BSW, 3/8BSW, r M10, M8, all x20mm, & M10x38 U16, 19 & 25mm
	Imported Un Hooded						
	UTWB75-138M	75	nylon	50	82	64	Plate 45mm sq
	UTWB75-7	75	nylon	50	82	64	Grip Neck
	UTWB75- *Threaded Pin	75	nylon	50	82	64	*3/8BSW, M10, all x20mm, & M10x38



BUSINESS NAME	
Caford NZ Ltd	Caford NZ Ltd

Ph: +649 444 8334
 Fx: +649 444 0784
 E-mail:
 sales@caford.co.nz
 www.caford.co.nz

Chair Base Castors And Glides

Imported
Design

EASILY MOVED - ECONOMICAL - ATTRACTIVE - LARGEST RANGE IN NEW ZEALAND

CODE	WHEEL DIA	CYLINDER DIA	MATERIAL	MAX LOAD	MOUNT HEIGHT	SWIVEL RADIUS	*FITTING
Imported Hooded Hard Wheel							
	mm	mm		KG	mm	mm	
CTW5038-77	50	38	Nylon	30	60	50	11mm clp C/
CTW5045-77	50	45	Nylon	30	60	50	11mm clp C/
CTW5050-77	50	50	Nylon	30	60	50	11mm clp C/
CTW6038-77	56	38	Nylon	35	70	60	11mm clp C/
CTW6045-77	56	45	Nylon	35	70	60	11mm clp C/
PG42SB-77		42	Nylon	35	15		*11mm clp C/
PG57SB-77		57	Nylon	35	45		*11mm clp C/
PG55SB-77		65	Nylon	35	60		*11mm clp C/



*Please note all the above glides can also be ordered with a Plate, threaded stem or grip neck stem for socket fixing in to



CAFORD CASTORS (NZ) LTD

Caford NZ Ltd

Chair Base Castors Friction Brake

Chap 1 Page 15

Volume 1, Issue 115

12 November 2013

Ph: +649 444 8334
 Fx: +649 444 0784
 E-mail:
 sales@caford.co.nz
 www.caford.co.nz

Imported
Design

EASILY MOVED - ECONOMICAL - ATTRACTIVE - LARGEST RANGE IN NEW ZEALAND

CODE	WHEEL DIA	CYLINDER DIA	MATERIAL	MAX LOAD	MOUNT HEIGHT	SWIVEL RADIUS	FITTING
TCTW5038FCHD-77 Friction Brake Chair Castor Hard Wheel Compression Release Brake	50	38	Nylon	30	60	50	11mm C/clip
TCTWRF5038-77SB Compression Apply Brake Hard Wheel Castor	50	38	Nylon	30	60	50	11mm C/clip
TCTW5038GBC-77 Friction Brake Chair Castor Soft Wheel Non Mark Grey PU Tyre Compression Release Brake	50	38	Nylon	30	60	50	11mm C/clip
	50	38	Nylon	30	60	50	11mm C/clip

TCTW5038FCHD-77



TCTWRF5038-77SB



TCTW5038GBC-77





CAFORD CASTORS (NZ) LTD

Caford NZ Ltd

Chap 1 Page 16

Volume 1, Issue 116




12 November 2013


Ph: +649 444 8334
 Fx: +649 444 0784
 E-mail: sales@caford.co.nz
 www.caford.co.nz

Metal Wheel Series Ball Castors For Loads Up To 45kg



Caford Design

EASILY MOVED - STYLISH - ATTRACTIVE - LARGEST RANGE IN NEW ZEALAND

	CODE	WHEEL Dia mm	MATERIAL	MAX LOAD KG	MOUNT HEIGHT mm	SWIVEL RADIUS mm	PLATE OR FITTING	Finish
	BC40-138M	40	ZINC	20	50	35	Plate 38mm sq	Chrome/ powder-coated
	BC40-7	40	ZINC	20	50	35	Grip Neck	As Above
	BC40-*Threaded Pin	40	ZINC	20	50	35	*5/16BSW, 3/8BSW, M10,M8, all x 20mm	As Above
	BC50-138M	50	ZINC	30	60	42	Plate 38mm sq	As Above
	BC50-7	50	ZINC	30	60	42	Grip Neck	As Above
	BC50-*Threaded Pin	50	ZINC	30	60	42	*5/16BSW, 3/8BSW, 3/8UNF, M10,M8, all x 20mm, 3/8UNF x 50mm Exp Socket Pin	As Above
	BC65-138M	65	ZINC	45	77	55	Plate 38mm sq	As Above
	BC65-7	65	ZINC	45	77	55	Grip Neck	As Above
	BC65-*Threaded Pin	65	ZINC	45	77	55	*5/16BSW, 3/8BSW, 3/8UNF, M10, all x 20mm 3/8UNF x 50mm Exp Socket Pin	As Above



For best results always fit as indicated below





CAFORD CASTORS (NZ) LTD

Caford NZ Ltd

Chap 1 Page 17

Volume 1, Issue 117




12 November 2013

Ph: +649 444 8334
 Fx: +649 444 0784
 E-mail:
sales@caford.co.nz
www.caford.co.nz

Polyurethane Tyre Series Ball Castors For Loads Up to 55kg




Caford Design

EASILY VED - NON MARKING - ATTRACTIVE - LARGEST RANGE IN NEW ZEALAND

	CODE	WHEEL Dia mm	MATERIAL	MAX LOAD KG	MOUNT HEIGHT mm	SWIVEL RADIUS mm	PLATE OR FITTING	Finish
	BCP57-138M	57	ZINC PLUS PU TYRE	25	65	45	Plate 38mm sq	Chrome
	BCP57-7	57	ZINC PLUS PU TYRE	25	65	45	Grip Neck	Chrome
	BCP57-* Threaded Pin	57	ZINC PLUS PU TYRE	25	65	45	*5/16BSW, 3/8BSW, 3/8UNF, M10, M8, all X 20mm 3/8UNF x 50mm Exp Socket Pin	Chrome
	BCP70-138M	70	ZINC PLUS PU TYRE	36	80	57	Plate 38mm sq	Chrome
	BCP70-7	70	ZINC PLUS PU TYRE	36	80	57	Grip Neck	Chrome
	BCP70-* Threaded Pin	70	ZINC PLUS PU TYRE	36	80	57	* 3/8BSW, 3/8UNF, all x 20mm & 3/8UNF x 50mm Exp Socket Pin	Chrome
	BCP100-138M	100	ZINC PLUS PU TYRE	55	111	80	Plate 45mm sq	Chrome
	BCP100-* Threaded Pin	100	ZINC PLUS PU TYRE	55	111	80	*1/2"UNF x 25mm & 3/8UNF x 50mm Exp Socket Pin	Chrome

THE METAL CASTOR WITH POLYURETHANE COMPOUND TYRE HAS OUTSTANDING RESISTANCE TO ABRASION AND IS UNAFFECTED BY OILS, ACIDS, ALKALIS, ETC. BEING RESILIENT, IT GIVES QUIET RUNNING ON HARD SURFACES AND HAS A LOAD CAPACITY ALMOST EQUAL TO METAL WHEELS. UNLIKE RUBBER IT WON'T PERISH !

For best results always fit as indicated below





CAFORD CASTORS (NZ) LTD

Caford NZ Ltd

Chap 1 Page 18

Volume 1, Issue 118

12 November 2013

Ph: +649 444 8334

Fx: +649 444 0784

E-mail:

sales@caford.co.nz

www.caford.co.nz

Castor Tube & Timber Sockets



**Nylon Castor
Grip Neck Socket**



**Metal Expanding
Socket**



Metal Grip Neck Socket

TUBE FITTINGS - NYLON

PRODUCT CODE	PINTLE NO.	OUTSIDE DIAMETER	TUBE GAUGE	INSIDE DIAMETER
N5	7	13mm ROUND	0.9mm	11.20mm
N6	7	19mm ROUND	1.2mm	16.60mm
N7	7	19mm ROUND	1.6mm	15.80mm
N1	7	19mm SQUARE	1.2mm	16.60mm
N4	7	22mm ROUND	1.6mm	18.80mm
N10	7	25.4mm ROUND	1.6mm	22.20mm
N9	7	25.4mm SQUARE	1.6mm	22.20mm
N3	7	28.5mm ROUND	1.6mm	25.30mm
N13	7	16mm ROUND	1.2mm	13.60mm
N14	7	25.4mm SQUARE	1.2mm	23.00mm
N15	7	25.4mm ROUND	1.2mm	23.00mm
N17	7	22mm ROUND	1.2mm	19.60mm
N18	7	22mm SQUARE	1.2mm	19.60mm

TUBE FITTINGS - METAL EXPANDING

T1	6	19mm ROUND	0.9-1.6mm	17.2-15.8mm
T9	6	19mm SQUARE	0.9-1.6mm	17.2-15.8mm
T2 plastic	6	22mm ROUND	0.9-1.6mm	20.2-18.8mm
T3 Plastic	6	25.4mm ROUND	0.9-1.6mm	23.6-22.2mm
T8 Plastic	6	25.4mm SQUARE	0.9-1.6mm	23.6-22.2mm
T4	6	32mm ROUND	0.9-1.6mm	30.2-28.8mm

TIMBER FITTINGS - NYLON

N5	7	11.1mm (27/64") DRILL SIZE
N8	7	11.2mm (7/16") DRILL SIZE
N2	5	12.7mm (1/2") DRILL SIZE
C337	12	10.3mm (3/8") DRILL SIZE
N24	50-111K+50-2D	NYLON SOCKET FOR PLN334 BEDLEG

TIMBER FITTINGS - METAL

N11	50/2	12.7mm (1/2") DRILL SIZE
N12	65/2	15.8mm (5/8") DRILL SIZE
C730	7	10mm Drill Size



Brass & Porcelain Wheeled Castors

CODE	DESCRIPTION
BRASSCUP30D	285B 30mm CUP CASTOR, 32mm BRASS WHEEL
BRASSCUP40E	286B 40mm CUP CASTOR AND 35mm BRASS WHEEL
BRASSCUP45G	287B 45mm CUP CASTOR WITH 50mm BRASS WHEEL
BRASSCUPSQ32H	290B 25mm SQUARE CUP WITH 32mm BRASS WHEEL
BRASSCREW25A	280B SCREW IN WITH 25mm BRASS WHEEL
BRASSCREW32B	281B SCREW IN WITH 32mm BRASS WHEEL
POR32SCREWPBWH	281W SCREW IN, WITH 32mm WHITE PORC. WHEEL
POR32SCREWPBBN	281BNSCREW IN, WITH 32mm BROWN PORC. WHEEL
PORCCUPSQ32WH	290W 30mmSQ CUP, 32mm WHITE PORCELAIN WHEEL
PORCCUPSQ32BN	290BN30mmSQ CUP, 32mm BROWN PORCELAIN WHEEL
PORCCUP32BNPD	285BN30mm CUP CASTOR, 32mm BROWN PORC. WHEEL
PORCCUP32WHPD	285W 30mm CUP CASTOR, 32mm WHITE PORC. WHEEL

